

R-AC/-HC Regular Duty Air or Hydraulic Cylinder Powered Precision Dovetail Slides



Standard Features

500 P.S.I. Hydraulic and 250 P.S.I. Air Working Pressure • Double Acting Non-Cushioned Cylinders For Quick-Action Movements and Repeatability

MODEL	SLIDE WIDTH	CARRIER HEIGHT	SLIDE HEIGHT	AVAILABLE LENGTHS				WEIGHT PER INCH OF CAST IRON	
				CARRIER		BASE		CARRIER	BASE
				MINIMUM	MAXIMUM	MINIMUM	MAXIMUM		
R-AC/-HC 2	2"	.75"	1.125"	4.4"	6"	3"	4"	.27 lbs.	.28 lbs.
R-AC/-HC 3	3"	.81"	1.250"	4"	6"	3"	4"	.43 lbs.	.50 lbs.
R-AC/-HC 4	4"	1.06"	1.625"	6.6"	12"	5"	9"	.75 lbs.	.88 lbs.
R-AC/-HC 6	6"	1.25"	1.875"	8"	16"	6"	12"	1.45 lbs.	1.38 lbs.

* R6 Slides furnished with lubrication ports.

- ▶ 7/8" Air Cylinder Bore and 1-1/16" Hydraulic Cylinder Bore on R2 Slides
 - ▶ 1-1/16" Air Cylinder and Hydraulic Cylinder Bore on R3 Slides
 - ▶ 1-1/4" Air Cylinder Bore and 1-1/2" Hydraulic Cylinder Bore on R4 Slides
 - ▶ 1-1/2" Air Cylinder and Hydraulic Cylinder Bore on R6 Slides

Accessories

Way Wipers • Accordion Type or Steel Covers • Compounding Tapered Gib • Nickel Plating • Special Cushioning and/or Valving



MILWAUKEE
SLIDE AND
SPINDLE

FAMCO MACHINE DIVISION

BELCO INDUSTRIES, INC.
1001-31st STREET
KENOSHA, WISCONSIN 53140
PHONE NO.: 1-262-654-3516
FAX NO.: 1-262-654-0803
e-mail: SALES@FAMCOMACHINE.COM